

1 2 3 4 5 6 7 8

Rev.	Description	Date	Drawn by	Checked by	Approved by
A	New Drawing	2006/01/02	Michael	Gavin	Stephen

NOTE:
Material and Finish:
 1. Housing: PBT (UL94V-0), White.
 2. Terminal: Phosphor Bronze, Gold Plating on Contact Area, Tin Plating on Solder Tail.
 3. Shield: Nickel Plating.
Electrical Characteristics:
 1. Current Rating: 1.5 Amp. Max..
 2. Dielectric Withstand Voltage: 500V AC RMS for 60Seconds.
 3. Insulation Resistance: 1000M Ohms Min. at 500V DC.
 4. Contact Resistance: 30m Ohms Max..
Mechanical Characteristics:
 1. Operating Temperature: -25°C ~ +85°C
 2. Contact Us for Customization.

Table 1

Part No.	Dimensions			
	Pos.	A	B	C
H=10.6mm AEUBGR02B-004F	4			

PCB Layout (Top View)
(Scale 2:1)

Tolerance 0.0 ±0.30 0.00 ±0.20 0.000 ±0.10	Drawn By Michael		
	Checked By Gavin		Title USB B Type, DIP Right Angle, 4P, Metal Shield, Female
	Approved By Stephen		AECOMM Technology Corp.

RoHS Compliant

Drawing No. UB002-S-01
Page 1/1

1 2 3 4 5 6 7 8